

AERIS 680



NEW 13.5 cm ultra-silent tacens fan (16dB) with antivibration pads



- EXCLUSIVE TACENS OdB TECHNOLOGY
 - REDUCES EFFECTIVELY THE HEAT PRODUCED BY THE POWER SUPPLY AND WITH AN INTELLIGENT FAN CONTROL, IT EVEN ALLOWS SWITCHING OFF THE PSU FAN WHEN IT IS NOT NEEDED, PRODUCING Odb NOISE.
- 100% COPPER CHASSIS AND COPPER PLATED HEATSINKS FOR MAXIMUM AND FASTEST HEAT DISSIPATION
- HIGH EFFICIENT ACTIVE POWER FACTOR CORRECTION (ACTIVE PFC)
- POWERFUL REAL 680W POWER
- PCI-EXPRESS, SLI, CROSSFIRE AND DUAL CORE CPU READY
- EPS 12V AND ATX12V 2.01 COMPLIANT WITH POWERFUL +12V DUAL RAILS
- MIRROR EFFECT FINISH AND LASER CUTTED TACENS LOGO
- INTELLIGENT BLACK CABLE SLEEVING
- EMI FILTERING IN PCI-EXPRESS CABLES FOR EMI PROTECTION
- CONNECTORS: 4x SATA, 20-24pin, ATX 2.01 4PIN / EPS 12V 8PIN, 8xHDD 4PIN, 2x FDD 4PIN, 2x PCI EXPRESS
- **NEW** tacens smart cable management to use only the cables you need

THIS NEW TACENS SMART CABLE MANAGEMENT SOLVES THE PROBLEMS OF ACTUAL SMART CABLE MANAGEMENTS WHEN YOU USE A LOT OF CONNECTORS. WITH THE NEW TACENS SMART CABLE MANAGENT YOU WILL ORGANIZE THE CABLES MUCH EASIER, CLEARED AND IN A MORE EFFECTIVE WAY.



- GREEN LIGHT SWITCH WHEN POWER ON
- FULL PROTECTION TECHNOLOGIES INCLUDED: IP, OVP, OPP, SCP FOR MAXIMUM SAFETY

AC INPUT	100-120Vac / 200-240 Vac 10 / 6A 60 / 50Hz					
DC OUTPUT	+3.3V	+5V	+12V1	+12V2	-12V	+5VSB
MAX OUTPUT CURRENT	32A	38A	22A	20A	0.8A	2.5A
MAX COMBINED WATTAGE	TAGE +3.3V+5V: 300W / +3.3V +5V +12V1 +12V2 -12V +5VSB: 680W					

